



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE2640

Silicon NPN Transistor

Color TV Horizontal Deflection Output

TO-220 Full Pack

Features:

- High Speed
- High Collector-Emitter Breakdown Voltage
- High Reliability
- On-Chip Damper Diode

Absolute Maximum Ratings: ($T_A + 25^\circ\text{C}$ unless otherwise specified)

Collector-Base Voltage, V_{CBO}	1500V
Collector-Emitter Voltage, V_{CEO}	800V
Emitter-Base Voltage, V_{EBO}	6V
Collector Current, I_C	
Continuous	6A
Pulse	15A
Collector Dissipation, P_C	
$T_A + 25^\circ\text{C}$	2W
$T_C + 25^\circ\text{C}$	30W
Operating Junction Temperature, T_J	+150°C
Storage Temperature Range, T_{stg}	-55° to +150°C

Electrical Characteristics: ($T_A + 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cutoff Current	I_{CBO}	$V_{CE} = 800\text{V}, I_E = 0$	–	–	10	μA
	I_{CES}	$V_{CE} = 1500\text{V}, R_{BE} = 0$	–	–	1.0	mA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 4\text{V}, I_C = 0$	40	–	–	mA
Collector-Emitter Sustaining Voltage	$V_{CEO(sus)}$	$I_C = 100\text{mA}, I_B = 0$	800	–	–	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 3.15\text{A}, I_B = 630\text{mA}$	–	–	3.0	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 3.15\text{A}, I_B = 630\text{mA}$	–	–	1.5	V
DC Current Gain	h_{FE}	$V_{CE} = 5\text{V}, I_C = 500\text{mA}$	10	–	–	
		$V_{CE} = 5\text{V}, I_C = 3.5\text{A}$	5	–	8	
Diode Forward Voltage	V_F	$I_{EC} = 6\text{A}$	–	–	2	V
Fall Time	t_f	$V_{CC} = 200\text{V}, V_{BE} = -2\text{V}, I_C = 2\text{A},$ $I_{B1} = 400\text{mA}, I_{B2} = 800\text{mA},$ Pulse Width = 20 μs , Duty Cycle $\leq 1\%$	–	–	0.3	μs

