

SANYO 7808
LA7612N

FM TANK(4.5V)	1	52	VCO TANK 2(6.7V)
LEFT IN(5.1V)	2	51	VCO TANK 1(6.7V)
IF AGC(7.6V)	3	50	LEFT OUT(3.7V)
RIGHT IN(5.1V)	4	49	FM TUNING(3.6V)
RF AGC OUT(3.3V)	5	48	RIGHT OUT(3.7V)
WBA OUT(3.7V)	6	47	IN IF(2.2V)
APC FILTER(3.6V)	7	46	BUS GND(0.0V)
IF GND(0.0V)	8	45	SOUND IF OUT(3.7V)
IN PIF(3.6V)	9	44	BUS DATA(4.9V)
IN PIF(3.6V)	10	43	BUS CLOCK(4.9V)
IF AGC IN(4.8V)	11	42	VIDEO OUT(3.4V)
AFT(4.8V)	12	41	TEST(5.4V)
CHROMA APC(5.6V)	13	40	CHROMA IN(2.8V)
XTAL(2.9V)	14	39	COLOR KILL(3.6V)
VERT.OUT(3.6V)	15	38	LUMA IN(3.8V)
RAMP ALC(3.8V)	16	37	BLK LEVEL DET(4.2V)
E/W OUT(3.5V)	17	36	BLUE IN(1.8V)
32H(4.6V)	18	35	GREEN IN(1.9V)
GND(0.0V)	19	34	RED IN(1.8V)
STBY VCC(7.5V)	20	33	FAST SW(0.0V)
HORIZ AFC(5.1V)	21	32	BLUE OUT(2.5V)
HORIZ OUT(3.0V)	22	31	GREEN OUT(2.5V)
FLY BACK(2.2V)	23	30	RED OUT(2.5V)
X-RAY IN(.06V)	24	29	ABL FILTER(2.2V)
AKB IN()	25	28	BEAM SENSE(6.3V)
VCC(7.5V)	26	27	GND(0.0V)