

**SCHOTTKY BARRIER RECTIFIERS**


REVERSE VOLTAGE - **20 to 200** Volts
FORWARD CURRENT - **1.0** Amperes

FEATURES

- Metal-Semiconductor junction with guard ring
- Epitaxial construction
- Low forward voltage drop
- High current capability
- The plastic material carries UL recognition 94V-0
- For use in low voltage,high frequency inverters,free wheeling,and polarity protection applications

MECHANICAL DATA

- Case : JEDEC DO-41 molded plastic
- Polarity : Color band denotes cathode
- Weight : 0.318 grams
- Mounting position : Any

DO-41

DO-41		
Dim.	Min.	Max.
A	25.4	-
B	4.20	5.20
C	0.70 $\varnothing$	0.90 $\varnothing$
D	2.00 $\varnothing$	2.70 $\varnothing$
All Dimensions in millimeter		

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

PARAMETER	SYMBOL	SB 120	SB 130	SB 140	SB 150	SB 160	SB 180	SB 1100	SB 1150	SB 1200	UNIT
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	80	100	150	200	V
Maximum RMS voltage	V _{RMS}	14	21	28	35	42	56	70	105	140	V
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	80	100	150	200	V
Maximum average forward rectified current	I _F	1.0									A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	30.0									A
Maximum Instantaneous Forward Voltage @ 1.0A	V _F	0.50			0.70		0.85		0.87	0.90	V
Maximum DC Reverse Current @ TA=25°C at Rated DC Blocking Voltage @ TA=100°C	I _R	0.5					0.2				mA
		10.0					2.0				
Typical Junction Capacitance	C _J	70			50		40		30		pF
Typical Thermal Resistance	R _{θJA}	70									°C/W
Operating Temperature Range	T _J	-55 to +125									°C
Storage Temperature Range	T _{STG}	-55 to +150									°C



FIG. 1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2-TYPICAL FORWARD CHARACTERISTICS




FIG. 3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 4-TYPICAL REVERSE CHARACTERISTICS




FIG. 5-TYPICAL JUNCTION CAPACITANCE

