

TOSHIBA TRANSISTOR SILICON NPN TRIPLE DIFFUSE TYPE (PCT PROCESS)

## 2SC4544

HIGH VOLTAGE SWITCHING AND AMPLIFIER APPLICATIONS

COLOR TV HORIZONTAL DRIVER APPLICATIONS


COLOR TV CHROMA OUTPUT APPLICATIONS

- High Voltage :  $V_{(BR)CEO} = 300V$
- Small Collector Output Capacitance :  $C_{ob} = 3.0pF$  (Typ.)
- Collector metal (Fin) is fully covered with mold resin.

MAXIMUM RATINGS ( $T_a = 25^\circ C$ )

| CHARACTERISTIC              |                    | SYMBOL    | RATING         | UNIT       |
|-----------------------------|--------------------|-----------|----------------|------------|
| Collector-Base Voltage      |                    | $V_{CBO}$ | 300            | V          |
| Collector-Emitter Voltage   |                    | $V_{CEO}$ | 300            | V          |
| Emitter-Base Voltage        |                    | $V_{EBO}$ | 7              | V          |
| Collector Current           |                    | $I_C$     | 100            | mA         |
| Base Current                |                    | $I_B$     | 50             | mA         |
| Collector Power Dissipation | $T_a = 25^\circ C$ | $P_C$     | 2              | W          |
|                             | $T_c = 25^\circ C$ |           | 8              |            |
| Junction Temperature        |                    | $T_j$     | 150            | $^\circ C$ |
| Storage Temperature Range   |                    | $T_{stg}$ | $-55 \sim 150$ | $^\circ C$ |

Unit in mm



Weight : 1.7g

ELECTRICAL CHARACTERISTICS ( $T_a = 25^\circ C$ )

| CHARACTERISTIC                       | SYMBOL        | TEST CONDITION                    | MIN. | TYP. | MAX. | UNIT    |
|--------------------------------------|---------------|-----------------------------------|------|------|------|---------|
| Collector Cut-off Current            | $I_{CBO}$     | $V_{CB} = 240V, I_E = 0$          | —    | —    | 1.0  | $\mu A$ |
| Emitter Cut-off Current              | $I_{EBO}$     | $V_{EB} = 7V, I_C = 0$            | —    | —    | 1.0  | $\mu A$ |
| DC Current Gain                      | $h_{FE(1)}$   | $V_{CE} = 10V, I_C = 4mA$         | 20   | —    | —    |         |
|                                      | $h_{FE(2)}$   | $V_{CE} = 10V, I_C = 20mA$        | 30   | —    | 200  |         |
| Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | $I_C = 10mA, I_B = 1mA$           | —    | —    | 1.0  | V       |
| Base-Emitter Saturation Voltage      | $V_{BE(sat)}$ | $I_C = 10mA, I_B = 1mA$           | —    | —    | 1.0  | V       |
| Transition Frequency                 | $f_T$         | $V_{CE} = 10V, I_C = 20mA$        | 50   | 70   | —    | MHz     |
| Collector Output Capacitance         | $C_{ob}$      | $V_{CB} = 20V, I_E = 0, f = 1MHz$ | —    | 3.0  | —    | pF      |

961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

